



Atlanta, Georgia

Phone 800-521-7326

Fax 770-745-1333

Nylon Cable Ties

Miniature Cable Ties - 18 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Minimum		Maximum		Material	Listed	UL Information			Unit	Catalog Page
				Thickness	Bundle Dia	Bundle Dia	Temp			Air Handling	Flame	Rating		
AL-04-18-O-C	705591000278	3.93"	0.09"	0.04"	.11"	.8"	-40 F	185 F	UV Black Nylon	UL Listed Type 21, UL 62275	UL AH-2	94V- 2	100	7-2
AL-04-18-O-M	705591000186	3.93"	0.09"	0.04"	.11"	.8"	-40 F	185 F	UV Black Nylon				1000	7-2
AL-04-18-9-C	705591000339	3.93"	0.09"	0.04"	.11"	.8"	-40 F	185 F	Natural Nylon				100	7-2
AL-06-18-O-C	705591001503	5.9"	0.09"	0.04"	.11"	1.43"	-40 F	185 F	UV Black Nylon				100	7-2

Intermediate Cable Ties - 40 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Minimum		Maximum		Material	Listed	UL Information			Unit	Catalog Page
				Thickness	Bundle Dia	Bundle Dia	Temp			Air Handling	Flame	Rating		
AL-05-40-9-C	705591002432	5.51"	0.14"	0.04"	0.14"	1.3"	-40 F	185 F	Natural Nylon	UL Listed Type 21, UL62275	UL AH-2	94V- 2	100	7-2
AL-05-40-O-C	705591002371	5.51"	0.14"	0.04"	0.14"	1.3"	-40 F	185 F	UV Black Nylon				100	7-2
AL-08-40-9-C	705591003637	8.0"	0.14"	0.04"	0.14"	2.07"	-40 F	185 F	Natural Nylon				100	7-2
AL-08-40-O-C	705591003576	8.0"	0.14"	0.04"	0.14"	2.07"	-40 F	185 F	UV Black Nylon				100	7-2
AL-11-40-O-C	705591004832	11"	0.14"	0.05"	0.14"	3.07"	-40 F	185 F	UV Black Nylon				100	7-2

Standard Cable Ties - 50 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Minimum		Maximum		Material	Listed	UL Information			Unit	Catalog Page
				Thickness	Bundle Dia	Bundle Dia	Temp			Air Handling	Flame	Rating		
AL-07-50-O-C	705591005587	7.87"	0.18"	0.05"	.14"	1.94"	-40 F	185 F	UV Black Nylon	UL Listed Type 21, UL 62275	UL AH-2	94V- 2	100	7-2
AL-07-50-O-M	705591005495	7.87"	0.18"	0.05"	.14"	1.94"	-40 F	185 F	UV Black Nylon				1000	7-2
AL-07-50-9-C	705591005648	7.87"	0.18"	0.05"	.14"	1.94"	-40 F	185 F	Natural Nylon				100	7-2
AL-07-50-9-M	705591005556	7.87"	0.18"	0.05"	.14"	1.94"	-40 F	185 F	Natural Nylon				1000	7-2
AL-11-50-O-C	705591006874	11.02"	0.18"	0.05"	.14"	2.94"	-40 F	185 F	UV Black Nylon				100	7-2
AL-11-50-O-D	705591006782	11.02"	0.18"	0.05"	.14"	2.94"	-40 F	185 F	UV Black Nylon				500	7-2
AL-11-50-9-C	705591006935	11.02"	0.18"	0.05"	.14"	2.94"	-40 F	185 F	Natural Nylon				100	7-2
AL-14-50-O-C	705591008106	14.56"	0.18"	0.05"	.14"	4.07"	-40 F	185 F	UV Black Nylon				100	7-2
AL-14-50-O-D	705591008014	14.56"	0.18"	0.05"	.14"	4.07"	-40 F	185 F	UV Black Nylon				500	7-2
AL-14-50-9-C	705591007987	14.56"	0.18"	0.05"	.14"	4.07"	-40 F	185 F	Natural Nylon				100	7-2
AL-17-50-O-C	705591009219	17.71"	0.18"	0.05"	.14"	5.08"	-40 F	185 F	UV Black Nylon				100	7-2
AL-17-50-9-C	705591009240	17.71"	0.18"	0.05"	.14"	5.08"	-40 F	185 F	Natural Nylon				100	7-2

Heavy Duty Cable Ties - 120 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Minimum		Maximum		Material	Listed	UL Information			Unit	Catalog Page
				Thickness	Bundle Dia	Bundle Dia	Temp			Air Handling	Flame	Rating		
AL-08-120-O-C	705591009363	8.60"	0.30"	.06"	.23"	2.2"	-40 F	185 F	UV Black Nylon	UL Listed Type 21	UL AH-2	94V- 2	100	7-2
AL-14-120-O-C	705591009639	15.09"	0.30"	.06"	.23"	4.06"	-40 F	185 F	UV Black Nylon				100	7-2
AL-14-120-9-C	705591009721	15.09"	0.30"	.06"	.23"	4.06"	-40 F	185 F	Natural Nylon				100	7-2
AL-18-120-O-L	705591010321	18.25"	0.30"	.06"	.23"	5.1"	-40 F	185 F	UV Black Nylon				50	7-2
AL-18-120-9-L	705591010291	18.25"	0.30"	.06"	.23"	5.1"	-40 F	185 F	Natural Nylon				50	7-2

Heavy Duty Cable Ties - 175 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Minimum		Maximum		Material	Listed	UL Information			Unit	Catalog Page
				Thickness	Bundle Dia	Bundle Dia	Temp			Air Handling	Flame	Rating		
AL-24-175-O-L	705591010741	24"	0.35"	.071"	.27"	7.15"	-40 F	185 F	UV Black Nylon	UL Listed 181B-C & Type 21	UL AH-2	94V- 2	50	7-2
AL-24-175-9-L	705591010802	24"	0.35"	.071"	.27"	7.15"	-40 F	185 F	Natural Nylon				50	7-2
AL-36-175-O-L	705591011229	36.2"	0.35"	.071"	.27"	11.00"	-40 F	185 F	UV Black Nylon				50	7-2
AL-36-175-9-L	705591011281	36.2"	0.35"	.071"	.27"	11.00"	-40 F	185 F	Natural Nylon				50	7-2
AL-48-175-O-L	705591011465	48"	0.35"	.071"	.27"	14.78"	-40 F	185 F	Natural Nylon				50	7-2

Air Handling Cable Ties - 50 LB Tensile Strength - RoHS Compliant - CSA Certified

Peco Catalog#	UPC	Length	Width	Minimum		Maximum		Color	Listed	UL Information			Unit	Catalog Page
				Thickness	Bundle Dia	Bundle Dia	Temp			Air Handling	Flame	Rating		
AL-07-50-AH-35-C	705591016330	7.87"	0.18"	0.05"	.14"	1.94"	-40 F	185 F	Burgandy	UL Listed Type 21S UL 62275	UL AH-2	94V- 2	100	7-2
AL-11-50-AH-35-C	705591016392	11.02"	0.18"	0.05"	.14"	2.94"	-40 F	185 F	Burgandy				100	7-2
AL-14-50-AH-35-C	705591016453	14.56"	0.18"	0.05"	.14"	4.07"	-40 F	185 F	Burgandy				100	7-2

Mounting Hole Cable Ties - 50 LB Tensile Strength - RoHS Compliant - CSA Certified

Item in Yellow Has A 120 LB Tensile Strength

											UL Information			Unit	Catalog	
Peco	Catalog#	UPC	Length	Width	Thickness	Minimum Bundle Dia	Maximum Bundle Dia	Minimum Temp	Maximum Temp	Material	Hole Screw Size	Listed	Air Handling Approved	Flame Rating	Size	Page
AL-07-50-MH-O-C		705591012073	8.00"	.18"	0.05"	0.06"	1.96"	-40 F	185 F	UV Black Nylon	#10 Screw	UL Listed Type 21, UL62275		94V-2	100	7-3
AL-07-50-MH-9-C		705591012097	8.00"	.18"	0.05"	0.06"	1.96"	-40 F	185 F	Natural Nylon	#10 Screw				100	7-3
AL-07-50-MH-9-C		705591012097	8.00"	.18"	0.05"	0.06"	1.96"	-40 F	185 F	Natural Nylon	#10 Screw				100	7-3
AL-11-50-MH-O-C		705591012370	12.0"	.18"	0.05"	0.06"	3.26"	-40 F	185 F	UV Black Nylon	#10 Screw				100	7-3
AL-14-50-MH-O-C		705591012554	14.50"	.18"	0.05"	0.06"	4.1"	-40 F	185 F	UV Black Nylon	#10 Screw				100	7-3
AL-14-120-MH-O-C		705591012677	15.75"	0.29"	0.07"	0.33"	4.25"	-40 F	185 F	UV Black Nylon	.25"				100	7-3

Adhesive Mounting Pads - RoHS Compliant - CSA Certified

												UL Information				
Peco					Slot		Slot		Mechanical Maximum		Hole		Air Handling	Flame	Unit	Catalog
Catalog#	UPC	Length	Width	Thickness	Width	Height	Strength	Temp	Material	Screw Size	Listed	Approved	Rating	Size	Page	
AL-MP-1000-O-C	705591015890	0.99"	0.99"	0.20"	0.20"	0.06"	11 LBS	158 F	UV Black Nylon	#6 Screw	UL Recognized Type 11		94V- 2	100	7-3	
AL-MP-1000-9-C	705591015937	0.99"	0.99"	0.20"	0.20"	0.06"	11 LBS	158 F	Natural Nylon	#6 Screw				100	7-3	
AL-MP-750-O-C	705591018594	0.76"	0.76"	0.20"	0.20"	0.06"	11 LBS	158 F	UV Black Nylon	#4 Screw				100	7-3	
AL-MP-750-9-C	705591159778	0.76"	0.76"	0.20"	0.20"	0.06"	11 LBS	158 F	Natural Nylon	#4 Screw				100	7-3	

Call Peco For Any Of Your Cable Tie Needs

Air Handling - Beaded Ties - Low Profile - Cold Weather - Colors - Double Head

Heat Stabilized - Identification - Metal Detectable - Push Mount - Releasable

Our Cable Ties Are Now Air Handling Approved Now By UL